

# AIR HYDRAULIC FOOT PUMPS

## B65425 10,000 PSI Air Foot Operated Pump

- Maximum working pressure 10,000 PSI
- High strength aluminum reservoir is light weight and corrosion resistant
- Suggested air pressure 110-175 PSI
- Pressure relief valve for overload protection
- Three-positions provide cylinder advance, hold, or retract operation
- A compact yet powerful Air Turbo Motor is equipped to raise the load to the desired height efficiently, effortlessly, and safely U.S. Patent No. 5,341,723



B65425

## B65426 10,000 PSI Air Foot Operated Pump

- Rugged construction built for long life and easy operation
- Swivel coupling simplifies hydraulic connection and pump operation
- Three-positions provide cylinder advance, hold, or retract operation
- Operates in any position
- Base mounting plate included
- A compact yet powerful Air Turbo Motor is equipped to raise the load to the desired height efficiently, effortlessly, and safely U.S. Patent No. 5,341,723



B65426

## B65427 10,000 PSI Air Foot Operated Pump

- Greater oil capacity to handle bigger jobs
- Maximum working pressure 10,000 PSI
- High strength aluminum reservoir is lightweight and corrosion resistant
- Suggested air pressure 110-175 PSI
- Pressure relief valve for overload protection
- Three-positions provide cylinder advance, hold, or retract operation
- A compact yet powerful Air Turbo Motor is equipped to raise the load to the desired height efficiently, effortlessly, and safely U.S. Patent No. 5,341,723



B65427

| Model Number | Usable Oil Capacity  | Rated Pressure | Output Flow Rate (In <sup>3</sup> /min.) |      | Input Air Pressure | Output Port Threads | Input Port Threads | G.W. (with fluid) |
|--------------|----------------------|----------------|------------------------------------------|------|--------------------|---------------------|--------------------|-------------------|
|              |                      |                | No Load                                  | Load |                    |                     |                    |                   |
| B65425       | 91.5 in <sup>3</sup> | 10,000 PSI     | 66                                       | 11   | 110-175 PSI        | 3/8"-18NPTF         | 1/4"-18 NPT        | 18 Lbs.           |
| B65426       | 36.6 in <sup>3</sup> |                | 61                                       | 9    |                    |                     |                    | 15 Lbs.           |
| B65427       | 122 in <sup>3</sup>  |                | 65                                       | 12   |                    |                     |                    | 20 Lbs.           |